

AeroGraphics

The Original Aircraft Lettering Company



Beechcraft 60 Duke Exterior Kit PAGE 1 of 1

NOTE: Modifications and changes to accommodate your specific aircraft will be made at **NO EXTRA CHARGE**.
Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

NO STEP NO STEP NO STEP NO STEP

DO NOT PUSH
DO NOT PUSH
FUEL CELL SUMP DRAIN
FUEL CELL SUMP DRAIN
FUEL CELL SUMP DRAIN
FUEL CELL SUMP DRAIN
FUEL STRAINER DRAIN
FUEL STRAINER DRAIN

DO NOT PUSH
DO NOT PUSH
TIE DOWN OXYGEN SERVICE
TIE DOWN TIE DOWN

NO HANDLE
NO HANDLE

EXTERNAL POWER 24 VOLTS
OXYGEN FILL INSIDE
JACK PAD
JACK PAD
JACK PAD
JACK PAD
JACK PAD

HEAT TREATED ASSEMBLY
HEAT TREATED ASSEMBLY
HEAT TREATED ASSEMBLY

IMPORTANT IMPORTANT
INSTALL DOOR LINK ROD BOLT WITH HEAD AFT INSTALL DOOR LINK ROD BOLT WITH HEAD AFT

STATIC AIR. KEEP CLEAN
STATIC AIR. KEEP CLEAN
STATIC AIR. KEEP CLEAN
STATIC AIR. KEEP CLEAN

FUEL SIGHT GAGE
FUEL SIGHT GAGE

FUEL CELL SUMP DRAIN DAILY
FUEL CELL SUMP DRAIN DAILY

INTERCONNECTED TANKS CHECK OUTBOARD FUEL LEVEL FIRST
INTERCONNECTED TANKS CHECK OUTBOARD FUEL LEVEL FIRST
INTERCONNECTED TANKS CHECK OUTBOARD FUEL LEVEL FIRST
INTERCONNECTED TANKS CHECK OUTBOARD FUEL LEVEL FIRST

FUEL
103.5 US GAL CAPACITY (101 US GAL USABLE)
FUEL
103.5 US GAL CAPACITY (101 US GAL USABLE)
FUEL SIGHT GAGE
FUEL SIGHT GAGE
FUEL SIGHT GAGE
FUEL SIGHT GAGE

WARNING
LUBRICATED BOLTS
WARNING
LUBRICATED BOLTS

DO NOT INSERT FUEL NOZZLE MORE THAN 3" INTO TANK
CAUTION
DO NOT INSERT FUEL NOZZLE MORE THAN 3" INTO TANK

UNLOCKED
LOCKED
OPEN
CLOSE

CAUTION
USE CARE WHEN WASHING WING TO NOT REMOVE ANTI-CORROSIVE GREASE FROM WING ATTACH BOLT

CAUTION
USE CARE WHEN WASHING WING TO NOT REMOVE ANTI-CORROSIVE GREASE FROM WING ATTACH BOLT

FUEL
102 US GAL CAPACITY (99 US GAL USABLE)
FUEL
102 US GAL CAPACITY (99 US GAL USABLE)

CAUTION
USE 100/130 GRADE FUEL OR HIGHER ONLY

CAUTION
USE 100/130 GRADE FUEL OR HIGHER ONLY

FUEL
103.5 US GAL CAPACITY (101 US GAL USABLE)
FUEL
118.5 US GAL CAPACITY (116.0 US GAL USABLE)

FUEL
103.5 US GAL CAPACITY (101 US GAL USABLE)
FUEL
118.5 US GAL CAPACITY (116.0 US GAL USABLE)

EMERGENCY EXIT

OPEN
1. PUSH BUTTON AND HOLD
2. TURN HANDLE TO OPEN

CLOSE

Beechcraft OIL AIR STRUT
BEECH CRAFT CORPORATION
INSTRUCTIONS
DO CHECK FLUID AND TIL...
RELEASE AIR IN TEST BEFORE REASSEMBLING

Beechcraft OIL AIR STRUT
BEECH CRAFT CORPORATION
INSTRUCTIONS
RELEASE AIR IN TEST BEFORE REASSEMBLING

Beechcraft OIL AIR STRUT
BEECH CRAFT CORPORATION
INSTRUCTIONS
RELEASE AIR IN TEST BEFORE REASSEMBLING

TOW
REMOVE RUBBER LOCK PRIOR TO TOWING

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065