

AeroGraphics

The Original Aircraft Lettering Company



Cessna 208 Caravan Exterior Kit PAGE 1 of 2

NOTE: Modifications and changes to accommodate your specific aircraft will be made at **NO EXTRA CHARGE**.
Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

ENGINE OIL

TOTAL CAPACITY 14 U.S. QUARTS
DRAIN & FILL 9.5 U.S. QUARTS

TYPE: SEE PILOT'S OPERATING HANDBOOK FOR APPROVED OILS. DO NOT MIX BRANDS

SERVICED WITH:

DOOR OPERATION:

TO OPEN ROTATE HANDLE	TO OPEN PUSH BUTTON & ROTATE HANDLE
TO CLOSE ROTATE HANDLE	TO CLOSE ROTATE HANDLE

LOCK OVERRIDE:

TO UNLOCK PULL & ROTATE KNOB	TO OPEN PULL HANDLE INBD & ROTATE
TO LOCK PULL & ROTATE KNOB	TO CLOSE ROTATE HANDLE & STOW

FUEL FILTER EPA CAN DRAIN
DRAIN DAILY PROPERLY DISPOSE

STATIC SOURCE DRAIN
OPEN CLOSED
MUST BE CLOSED FOR FLIGHT

REFILL WITH MIL-H-5606 FLUID WHEN RESERVOIR REACHES 1/2 FULL. REFILL TO WITHIN 3/4 OF .098 DIA. VENT HOLE.

BRAKE FLUID RESERVOIR
MAX
MIN

BRAKE FLUID RESERVOIR
REFILL WITH MIL-H-5606 FLUID
MAX
MIN

BRAKE FLUID RESERVOIR
REFILL WITH MIL-H-5606 FLUID
MAX
MIN

JET-A-FUEL
TOTAL CAPACITY 167.5 U.S. GALLONS
ANTI-ICE ADDITIVE REQUIRED. SEE PILOTS OPERATING HANDBOOK FOR OTHER APPROVED FUELS, QUANTITY AND TYPE OF ADDITIVE.
- GROUND TO WING TIE-DOWN FITTING.

JET-A-FUEL
TOTAL CAPACITY 167.5 U.S. GALLONS
ANTI-ICE ADDITIVE REQUIRED. SEE PILOTS OPERATING HANDBOOK FOR OTHER APPROVED FUELS, QUANTITY AND TYPE OF ADDITIVE.
- GROUND TO WING TIE-DOWN FITTING.

AEROGRAFICS
1405 N. PROSPECT DR.
LOVELAND, CO 80538
800-336-9633

CESSNA 208-2088
EXTERIOR KIT

EXTERNAL POWER
28 VOLTS D.C. NOMINAL
800 AMP
STARTING CAPACITY MIN.
DO NOT EXCEED 1700 AMPS

WARNING **WARNING** OXYGEN
MAXIMUM MAXIMUM FILLER
TOW TOW DOOR
LIMIT LIMIT

EXTERNAL POWER
28 VOLTS D.C. NOMINAL
800 AMPS
STARTING CAPACITY MIN.
DO NOT EXCEED 700 AMPS

CAUTION
DO NOT TOW AIRCRAFT WITH RUDDER LOCK ENGAGED

FLUX VALVE
USE NON-MAGNETIC TOOLS AND SCREWS

WARNING
OUTSIDE PROXIMITY OF LOWER DOOR MUST BE CLEAR BEFORE OPENING

CAUTION
DO NOT TOW AIRCRAFT WITH RUDDER LOCK ENGAGED

UNLOCK LOCK
BEFORE TAXI AND FLIGHT UNLOCK

UNLOCK LOCK
BEFORE TAXI AND FLIGHT UNLOCK

WARNING
ELT IS LOCATED BEHIND THIS SURFACE

WARNING
OUTSIDE PROXIMITY OF LOWER DOOR MUST BE CLEAR BEFORE OPENING

CAUTION 24 VOLTS D.C.
THIS AIRCRAFT IS EQUIPPED WITH GENERATOR AND A NEGATIVE GROUND SYSTEM

OBSERVE PROPER POLARITY
REVERSE POLARITY WILL DAMAGE ELECTRICAL COMPONENTS.

CAUTION 24 VOLTS D.C.
THIS AIRCRAFT IS EQUIPPED WITH GENERATOR AND A NEGATIVE GROUND SYSTEM

OBSERVE PROPER POLARITY
REVERSE POLARITY WILL DAMAGE ELECTRICAL COMPONENTS.

JET-A-FUEL
TOTAL INBD CAPACITY 120.0 U.S. GALLONS

ANTI-ICE ADDITIVE REQUIRED. SEE PILOT'S OPERATING HANDBOOK FOR OTHER APPROVED FUELS, QUANTITY AND TYPE OF ADDITIVE GROUND TO WING TIE-DOWN FITTING

CAUTION
DO NOT OPEN WHEN FUEL QUANTITY IS IN EXCESS OF 120.0 U.S. GALLONS.

DOOR OPERATION

DOOR OPERATION LATCHED CLOSE OPEN	DOOR OPERATION LATCHED CLOSE OPEN
--	--

JET-A-FUEL
TOTAL INBD CAPACITY 120.0 U.S. GALLONS

ANTI-ICE ADDITIVE REQUIRED. SEE PILOT'S OPERATING HANDBOOK FOR OTHER APPROVED FUELS, QUANTITY AND TYPE OF ADDITIVE GROUND TO WING TIE-DOWN FITTING

CAUTION
DO NOT OPEN WHEN FUEL QUANTITY IS IN EXCESS OF 120.0 U.S. GALLONS.

DOOR OPERATION

TO OPEN PUSH BUTTON & ROTATE HANDLE	TO CLOSE ROTATE HANDLE
--	------------------------------

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065



Cessna 208 Caravan Exterior Kit PAGE 2 of 2

NOTE: Modifications and changes to accommodate your specific aircraft will be made at **NO EXTRA CHARGE**.
Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065



JET-A-FUEL
TOTAL CAPACITY 167.5 U.S. GALLONS
ANTI-ICE ADDITIVE REQUIRED. SEE PILOTS
OPERATING HANDBOOK FOR OTHER APPROVED
FUELS, QUANTITY AND TYPE OF ADDITIVE.
- GROUND TO WING TIE-DOWN FITTING.

JET-A-FUEL
TOTAL CAPACITY 167.5 U.S. GALLONS
ANTI-ICE ADDITIVE REQUIRED. SEE PILOTS
OPERATING HANDBOOK FOR OTHER APPROVED
FUELS, QUANTITY AND TYPE OF ADDITIVE.
- GROUND TO WING TIE-DOWN FITTING.

NO PUSH NO PUSH
NO STEP NO STEP
NO LIFT NO LIFT

LOCKED

OPEN



DOOR OPERATION

TO OPEN
PUSH BUTTON &
ROTATE
HANDLE

TO CLOSE
ROTATE
HANDLE

JET-A-FUEL
MAX PRESSURE 50 P.S.I.
ANTI-ICE ADDITIVE REQUIRED. SEE PILOT'S OPERATING
HANDBOOK FOR OTHER APPROVED FUELS, QUANTITY
AND TYPE OF ADDITIVE.
GROUND TOWING TIE DOWN FITTING

JET-A-FUEL
MAX PRESSURE 50 P.S.I.
ANTI-ICE ADDITIVE REQUIRED. SEE PILOT'S OPERATING
HANDBOOK FOR OTHER APPROVED FUELS, QUANTITY
AND TYPE OF ADDITIVE.
GROUND TOWING TIE DOWN FITTING

**D
A
N
G
E
R
O
P
O
R
T
A
R
E
A**

**D
A
N
G
E
R
O
P
O
R
T
A
R
E
A**

CAUTION

**BFG. "L" KIT APPLIED TO POD BUD
DO NOT APPLY "AGE MASTER"**

CAUTION

**BFG. "L" KIT APPLIED TO POD BUD
DO NOT APPLY "AGE MASTER"**

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065