

AeroGraphics

The Original Aircraft Lettering Company



Rockwell Commander 500U Shrike Exterior Kit

PAGE 1 of 1

NOTE: Modifications and changes to accommodate your specific aircraft will be made at NO EXTRA CHARGE. Partial kits available upon request.

IF YOU HAVE ANY QUESTIONS PLEASE CALL!

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065

<p>AVGAS ONLY</p> <p>GRADE 100  GRADE 100LL</p> <p>MAIN TANK US GAL</p>	<p>COMMANDER 500S SHRIKE EXTERIOR PAGE 1 OF 1</p> <p>STATIC AIR STATIC AIR KEEP CLEAN KEEP CLEAN</p>	<p>AVGAS ONLY</p> <p>GRADE 100LL  GRADE 100</p>	<p>FUEL TANK SUMP DRAIN</p> <p>STATIC VENTS KEEP CLEAR</p> <p>STATIC VENTS KEEP CLEAR</p>	<p>OIL FILL ACCESS CONFIRM CORRECT OIL AND QUANTITY</p> <p>TANK-SUMP DRAIN DAILY</p>
<p>AVGAS ONLY</p> <p>GRADE 100  GRADE 100LL</p> <p>MAIN TANK US GAL</p>	<p>AVGAS 100 LL 156 GAL CAP</p> <p>CAUTION USE 100,130 GRADE OR HIGHER</p> <p>NO PUSH NO PUSH</p>	<p>WARNING TO ASSURE PROPER FUEL LEVEL, ALLOW EXTENDED FUELING TIME TO EQUALIZE FUEL LEVEL AMONG THE INTERCONNECTED TANKS</p>	<p>BATTERY ACCESS</p> <p>BAGGAGE ACCESS</p>	<p>PUSH IN ► TO OPEN</p> <p>PUSH ►</p>
<p>0 1 2 3 4 5 6 7 8 9 . 0 1 2 3 4 5 6 7 8 9 . 0 1 2 3 4 5 6 7 8 9 . 0 1 2 3 4 5 6 7 8 9 .</p>	<p>OXYGEN FILLER AVIATORS BREATHING OXYGEN PER MIL-O-27210 SEE SERVICE MANUAL FOR SERVICE INSTRUCTIONS USE NO OIL</p> <p>GROUND GROUND HERE HERE</p> <p>JACK PAD JACK PAD</p>	<p>OIL FILL ACCESS CONFIRM CORRECT OIL AND QUANTITY</p> <p>EXT. POWER RCPT. 24 VOLTS D.C.</p> <p>LEVEL POINT PITOT LEVEL POINT DO NOT OBSTRUCT DO NOT OBSTRUCT</p>	<p>NO STEP NO STEP</p> <p>NO HAND HOLD</p> <p>HAND HOLD</p>	<p>PUSH IN ► TO OPEN</p> <p>PUSH ►</p> <p>FUEL TANK SUMP DRAIN</p> <p>LOCATOR BEACON DISARM SWITCH TEST AND EMERGENCY</p>
<p>OPEN STOW LOCK STOW LOCK</p>	<p>DISENGAGE RUDDER & CONTROL LOCKS BEFORE GROUND HANDLING</p> <p>EMERGENCY EXIT</p> <p>CAUTION TOW LIMITS CAUTION TOW LIMIT</p>	<p>← NOSE WHEEL TURN LIMIT</p> <p>NOSE WHEEL TURN LIMIT →</p>		

Phone: 1-800-336-9633 www.aerographics.com Fax: 1-970-461-2065