

# AeroGraphics

The Original Aircraft Lettering Company



## Piper PA-28R Interior Kit PAGE 1 of 2

NOTE: Modifications and changes to accommodate your specific aircraft will be made at **NO EXTRA CHARGE**.  
Partial kits available upon request.

**IF YOU HAVE ANY QUESTIONS PLEASE CALL!**

Phone: 1-800-336-9633    www.aerographics.com    Fax: 1-970-461-2065

**GEAR**  
UP 109 KIAS MAX  
DOWN 130 KIAS MAX

**GEAR**  
UP 125 MPH MAX  
DOWN 150 MPH MAX

**RAD LIGHT**

**AIR COND DOOR OPEN**

**LOCK BEFORE PRIMER FLIGHT**

**PARK BRAKE PULL**

**AIR COND. CONTROL**  
AIR COND. FAN TEMP.  
ON HI OFF LOW COOLER  
OFF OFF WARNING

AIR CONDITIONER MUST BE OFF PRIOR TO TAKE-OFF AND LANDING

FUEL REMAINING WHEN THE QUANTITY INDICATED READ ZERO CANNOT BE USED SAFELY IN FLIGHT

**DN** ELEC. PITCH TRIM PUSH - ON/OFF  
**N** OUTER MIDDLE INNER MASTER  
**UP** ENGAGE LATCH BEFORE FLIGHT  
MANEUVERING SPEED 134 MPH

RMI MASTER HEAT FAN

**WARNING**  
EMERGENCY LOCATOR TRANSMITTER FOR AVIATION EMERGENCY USE ONLY UNLICENSED OPERATION UNLAWFUL OPERATION IN VIOLATION OF FCC RULES SUBJECT TO FINE OR LICENSE REVOCATION  
PULL TO RESET ON (RESET) ARM

**OPEN** ENGAGE LATCH BEFORE FLIGHT **CLOSE**

**AUTOFLIGHT II**  
TURN AUTOFLIGHT ON. ADJUST "TRIM" KNOB FOR MINIMUM HEADING CHANGE. FOR HEADING CHANGE, PRESS DISENGAGE SWITCH ON CONTROL WHEEL, CHANGE HEADING' RELEASE SWITCH.

ROTATE "TURN" KNOB FOR TURN COMMANDS, PUSH "TURN" KNOB IN TO ENGAGE TRACKER. PUSH "TRIM" KNOB IN FOR "HI" SENSITIVITY. AUTOFLIGHT OFF FOR TAKEOFF & LANDING.

**FUEL ON PROPER TANK**  
AUX. FUEL PUMP OFF  
ENGINE GAGES CHECKED  
SEAT BACKS ERECT

**TAKE OFF CHECKLIST**  
MIXTURE SET  
PROPPELLER SET  
FASTEN BELTS / HARNESS

**FLAPS SET**  
TRIM TAB SET  
CONTROLS FREE  
AIR CONDITIONER OFF

**FUEL ON PROPER TANK**  
SEAT BACKS ERECT  
FASTEN BELTS / HARNESS

**LANDING CHECKLIST**  
AUX. FUEL PUMP OFF  
PROPPELLER SET

**GEAR-DOWN** (133 KIAS MAX)  
FLAPS SET (108 KIAS MAX)  
AIR CONDITIONER OFF

**AEROGRAPHICS**  
1405 N. PROSPECT DR.  
Loveland, CO 80538  
800-336-9633

**PIPER PA28 ARROW**  
**INTERIOR KIT**  
**1 OF 3**

ROUGH AIR OR MANEUVERING SPEED 120 MPH

**PILOT** **CO-PILOT** **INTER-COM**

**TAKEOFF CHECKLIST**  
FUEL-ON PROPER TANK  
ELECTRIC FUEL PUMP-ON  
ENGINE GAGES-CHECKED

**PROP-SET**  
MIXTURE-SET  
FLAP-SET

**TRIM TAB-SET**  
CONTROLS-FREE  
DOOR-LATCHED

**LANDING CHECKLIST**  
FUEL-ON PROPER TANK  
ELECTRIC FUEL PUMP-ON

**MIXTURE-SET**  
PROP-SET

**GEAR-DOWN** (150 M.P.H. MAX)  
FLAPS-SET (125 M.P.H.)

**FUEL ON PROPER TANK**  
ELECT. FUEL PUMP ON  
ENGINE GAGES CHECKED  
SEAT BACKS ERECT

**TAKE OFF CHECKLIST**  
PRIMER LOCKED  
MIXTURE SET  
PROPPELLER SET  
FASTEN BELTS / HARNESS

**FLAPS SET**  
TRIM TAB SET  
CONTROLS FREE  
DOORS LATCHED  
AIR CONDITIONER OFF

**SEAT BACKS ERECT**  
FASTEN BELTS / HARNESS  
FUEL ON PROPER TANK

**LANDING CHECKLIST**  
ELECTRIC FUEL PUMP ON  
MIXTURE RICH

**PROPPELLER SET**  
FLAPS SET - WHITE ARC  
AIR CONDITIONER OFF

**WARNING**  
ALL MASK AND CONNECTORS INSTALLED MUST BE IN USE

**WARNING**  
FUEL GAGES MAY INDICATE AS MUCH AS 2 1/2 GALLONS WHEN TANKS ARE EMPTY.

**WARNING**  
LOWERING CONDENSER BEYOND CYCLE LIMIT WILL DAMAGE CONNECTED REFR. LINES

**OFF** **OFF** **OFF** **OFF** **OFF** **OFF** **ON** **ON** **GPS**

**CAUTION**  
ALL GLIDE SLOPE INDICATORS DISPLAY NAV 1 SIGNAL

**N S D**  
360A

**AUTO PILOT**

**THROTTLE PUSH OPEN**

**MIXTURE FULL LEAN**

**COMPASS SYSTEM**

**PITOT - STATIC SYSTEM DRAIN**

**DEMONSTRATED CROSSWIND COMPONENT 20 MPH**

**NO HEAVY OBJECTS ON HAT SHELF**

**HEAT UP TO ACTUATE ON DEF**

**THIS AIRCRAFT APPROVED FOR NIGHT I.F.R., NON-ICING FLIGHT WHEN EQUIPPED IN ACCORDANCE WITH FAR 91 OR FAR 135.**

**THIS AIRCRAFT MUST BE OPERATED AS A NORMAL CATEGORY AIRPLANE IN COMPLIANCE WITH THE OPERATING LIMITATIONS STATED IN THE FORM OF PLACARDS, MARKINGS AND MANUALS.**

**OPEN THROTTLE**  
**INCR PROP RPM**  
**RICH MIXTURE**  
**DEC R LEAN**  
**CLOSE**

**NOSE TRIM**  
DN UP

**NOSE TRIM**  
L R

**NAV 2**

	65%	75%
SL	2250	2375
4000	2350	2490
8000	2440	2600

**DEMONSTRATED CROSSWIND COMPONENT 17 KNOTS**

**TAKEOFF CHECK LIST**  
FUEL ON PROPER TANK  
AUXILIARY FUEL PUMP OFF  
ENGINE GAGES CHECKED  
ALTERNATE AIR CLOSED  
SEAT BACKS ERECT  
MIXTURE SET  
PROPPELLER SET

**FASTEN BELT & HARNESS**  
FLAPS SET  
TRIM TAB SET  
CONTROLS FREE  
DOORS LATCHED  
AIR CONDITIONER OFF

**LANDING CHECK LIST**  
FUEL ON PROPER TANK  
SEAT BACKS ERECT  
FASTEN BELT & HARNESS  
AUX. FUEL PUMP OFF  
MIXTURE RICH

**PROPPELLER SET**  
GEAR DOWN (133 KIAS MAX.)  
FLAPS SET (108 KIAS MAX.)  
AIR CONDITIONER OFF

**GEAR-DOWN** 133 KIAS (MAX)  
GEAR-DOWN 111 KIAS (MAX)  
EXTENDED 133 KIAS (MAX)

**CRUISE FUEL FLOWS ARE APPROXIMATE**

**DME NAV 1**  
AVOID CONTINUOUS GRND. OPER. 100-2100 RPM IN CROSS/TAIL WIND OVER 10KT

**MANEUVERING SPEED**  
124 KIAS AT 2800 LBS. (SEE A.F.M.)

**NAV 2**  
AVOID CONTINUOUS OPERATION 2000-2200 RPM ABOVE 32" MANIFOLD PRESSURE

**BAT**  
**ALT**

**OIL COOLER WINTERIZATION PLATE TO BE REMOVED WHEN AMBIENT TEMPERATURE EXCEEDS 50° F**

**NAV 1**

**FAN**  
HI  
LOW

**PARK BRAKE PUSH**

Phone: 1-800-336-9633    www.aerographics.com    Fax: 1-970-461-2065

